


01CYD0934

Light Source	9x0.5W
Lens	N/A
Selected Degree (°)θ1/2	N/A
Input Voltage (V)	DC 24 AC 240
Operating Current (MA)	24V=250 240V=46
Consumption (W)	24V=6 240V=6.3
Luminance (LM)	WW=199
IK	07

Linear Drawing




Unit: mm

Specification

Front Cover & Housing	12# Die-casting RAL9005 powder coated aluminum T=60-80um.Adhesion of ISO class 1/ASTM class 4B
Light Window	Tempered glass
Gasket	Waterproof silicone gasket
Cable Gland	IP67
LED Type	SMD
Driver	Built in on/off driver
Recessed Sleeve	Option 1: PC/ABS ALLOYS 150# Option 2: Material SUS 202#
Operating Temperature	-20°C~40°C
Power Cable	Outside of luminaire (Without waterstopper) DC power: H05RN-F 2×1.0mm², L=0.3m(24V) AC power: H05RN-F 3×1.0mm², L=0.3m(240V)
Dimming Support	External DALI supported TRIAC,0-10V, PWM via external driver on request


Painting Color

Primary




Sanded Black
RAL 9005

Secondary




Sanded Dark Grey
KAP 7037



Sanded White
RAL 9003


Sleeve



Sleeve 150#




Features

Screwless front cover





Use the high-strength clips for fixation.
(please refer remark ① & ②)

Diagram Of Instruction



Photometric

12m	0.02 LUX
11m	
10m	0.03 LUX
9m	
8m	0.05 LUX
7m	
6m	0.10 LUX
5m	
4m	0.21 LUX
3m	
2m	0.86 LUX
1m	



Lux distance curve

Center beam LUX	Beam width V	Beam width H
2m 0.86 LUX	4.9m	1.7m
4m 0.21 LUX	9.9m	3.4m
6m 0.10 LUX	14.8m	5.1m
8m 0.05 LUX	19.7m	6.8m
10m 0.03 LUX	24.6m	8.5m
12m 0.02 LUX	29.6m	10.2m

Ver.Spread:101.9 Horiz.Spread:46.0