

03EMKB0957

Light Source	9x1.8W
Lens	B116
Selected Degree(°)Ø1/2	35°
Input Voltage (V)	DC 24 AC 120 240
Operating Current (mA)	24V=750 120V=146 240V=17
Consumption (W)	24V=18 120V=17.5 240V=17
Luminance (LM)	WW=1570
IK	06

Specification

Housing	12# Die-casting Sanded Dark Grey powder coated aluminum T=60-80µm Adhesion of ISO class 1/ASTM class 4B
Light Window	Tempered glass T=3mm
Gasket	Tooling shaped seal
LED Type	SMD
Driver	Built in on/off driver
Operating Temperature	-20°~40°C
Power Cable	Outside of luminaire (Without waterstopper) 24V: H05RN-F 2×1.0mm², L=2.0m 120V/240V: H05RN-F 3×1.0mm², L=2.0m
Dimming Support	External DALI supported TRIAC, 0-10V, PWM via external driver on request

Optional (Accessories)

Spike
PC/ABS alloys



17A

Ø79



276

Stainless steel



13A

Ø79




266

Bevel Cut Hood



CA3023



120

43.5



Water Proof Solution




A Water stopper(Included)

The luminaires produce high temperatures during use, which can create negative pressure upon power-off, drawing water vapor through the power cable. Therefore, it is essential for the device to prevent water vapor ingress with water-stopper.

B IP67 Jiffy quick plug/socket connector(Option)

Along with water-stopper, this optional accessory acts as a fail-safe device for preventing vapor getting into the fixture via power cable. It is the also the most IP-rating securing device for wiring.

Linear Drawing



Unit: mm

Lens (Item Code)

Referenced Degree(°)Ø1/2



B116

20° 40° 60°

Painting Color

Primary



Sanded Bronze
KAP 7008

Secondary



Sanded Dark Grey
KAP 7037



Sanded Black
RAL 9005