


# 09ADHD4234A

# Linear Drawing

Height (mm)	800
Light Source	42x0.2W
Input Voltage (V)	DC 24 AC 120 240
Operating Current (MA)	24V=415 120V=76 240V=38
Consumption (W)	24V=10 120V=8.6 240V=8.2
Luminance (LM)	VVV=586
IK	07



## Specification

Housing	12# Die-casting aluminum powder coated. T=60-80µm Adhesion of ISO class 1/ASTM class 4B
Light Window	PMMA
LED Type	SMD
LED Driver	Built in on/off driver
Operating Temperature	-20°C~40°C
Power Cable	Outside of luminaire (Without waterstopper) 24V: H05RN-F 2×1.0mm <sup>2</sup> , L=0.5m 120V/240V: H05RN-F 3×1.0mm <sup>2</sup> , L=0.5m
Base	Flange base
Dimming Support	External DALI supported TRIAC,0-10V, PWM via external driver on request

## Painting Color

Primary		Sanded Black RAL 9005
Secondary		Sanded Dark Grey KAP 7037
		Sanded Bronze KAP 7008


## Modular Light Source and Power with IP-66



- 1 IP66 light source module with pc cover
- 2 IP66 built-in power module
- 3 IP67 cable gland

## Base Options

Source Mounting Base	Inground Base (Optional)	Ground Anchor Base (Optional)
<p>Type A Flange Base Non-Detachable</p>	<p>JC3001</p>	<p>22A</p> <p>Installation steps (Optional)</p>
<p>Type B Non-flange Base Detachable</p>	<p>JC3002</p>	<p>25A</p> <p>Installation steps (Optional)</p>



## Photometric

